

DECLARATION OF PERFORMANCE

In accordance with Regulation (EU) No 305/2011 of the European Parliament and of the Council laying down harmonised conditions for the marketing of construction products (CPR EU 305/2011)

No. HPL 001 28-06-13

1. Unique identification code of the product-type:

Fibre Cement Flat Sheet

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

HardiePlank®

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Fibre cement cladding for exterior and interior walls

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**James Hardie Building Products
17 Unytite Drive
Peru
Illinois
61354
USA**

**James Hardie Building Products
1000 James Hardie Way
Pulaski
Virginia
24301
USA**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

**James Hardie Building Products Ltd
7, Albemarle Street
London
W1S 1HQ**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

Level 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

Type testing carried out by:

James Hardie Pty Ltd. 10 Colquhoun St, Rosehill NSW 2142, Australia

Reaction to fire tested by:

EXOVA WARRINGTONFIRE. Holmesfield Road, WA1 2DS, Warrington, United Kingdom

Notified Body no. 0833

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

N/A

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

General Property	Unit or Characteristic	Result	Test Method
Dimensional tolerances		Level 1	EN 12467:2012
Average density	Saturated, g/cm ³	1.3	
Water Impermeability	Physical Observations	Pass	
Modulus of rupture (MPa)	Saturated average MPa	8.5MPa	
Type, Category, Class		NT Category A Class 2	
Warm Water Evaluation		Pass	
Freeze/Thaw Resistance			
Soak/dry			
Heat/Rain Resistance			
Surface Burning Characteristics	Fuel Contributed	A2	
	Smoke Development Index	s1	
	Flames Droplets Index	d0	
Release of dangerous substances		NPD	

10. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:


Mr M Longfellow – General Manager Europe


Amsterdam, 1 July 2013

(insert place and date of issue)



(insert signature)

	<p>Fibre cement cladding for exterior and interior walls</p> <p>Type of sheets NT: Category A Class 2 Size: 3600 x 180mm x 8mm Mechanical resistance: 8.5MPa Apparent density: 1.3 Reaction to fire: A2 - s1, d0 Release of dangerous substances: NPD Water Impermeability: Pass Water vapour permeability: N/A Dimensional variations: Level 1 Durability against warm water: Pass Durability against soak-dry: Pass Durability against freeze-thaw: Pass Durability against heat-rain: Pass</p>
<p>HardiePlank</p>	
<p>James Hardie Building Products Ltd 7, Albemarle Street London W1S 1HQ</p>	
<p>DOP No. HP 001 28-06-13</p>	
<p>EN12467:2012 Fibre-cement flat sheets Product specification and test methods</p>	



James Hardie